



SYM.	DATE	DESCRIPTION	REV. BY
	09.03.23	接続部材質追加、一部寸法変更	TANABE

大きさ SIZE	a	b	E	H
75	16.5	42	83	102.5
100	18.5	48	107.5	130

JIS10kgf/cm<sup>2</sup>

	10A	15A	20A	25A	40A	50A
C	65	70	75	90	105	120
D	90	95	100	125	140	155
t	12	12	14	14	16	16
h	15	15	15	19	19	19
g	46	51	56	67	81	96
f	1	1	1	1	2	2

※  
 FF フランジ \_\_\_\_\_  
 FF FLANGE  
 RF フランジ \_\_\_\_\_  
 RF FLANGE

⑥	Diaphragm ダイヤフラム	SUS316L . PTFE			
⑤	Lower Flange 下フランジ	SUS304 . SUS316		Order No. 貴注番	
④	Upper Flange 上フランジ	SUS304		Scale Range 目盛範囲	MP a
③	Socket 接続部	SUS		Quantity 台数	
②	Case ケース	SUS304	Polish Electrolysis 電解研磨	Flange Size フランジ呼び径	
①	Cover カバー	SUS304	Polish Electrolysis 電解研磨	Remarks 備考	
No.	Name 部品名	Material 材質	Finish 処理		
MATERIAL 材質		DESIGNED FOR Diaphragm-Seal Type Pressure Gauge (All Stainless Steel Type) 品名 PK 隔膜式圧力計 (オールステンレス製)		PLATES NO. 品番	MODELS TO BE USED QTY.
FINISH 処理		MODEL AND SIZE 型名 PK-5 A φ75. φ100		DATE 2008.02.18	CHKD. KOTSUNA
SCALE 尺度 Free		TOLERANCE 公差 ±		DRWN. TANABE	APPD. OHANA
		TITLE 図名 Outside Drawing 外形図		DRWG NO. 図番 PD17AUSY000 PK5-001	

