



d	f	F
1/4	16	78
3/8	18	80
1/2	20	82

接点容量			
	電圧	AC定格電流	DC定格電流
A	30V	—	1A
	125V	7.5A	—
	250V	7.5A	—
B1	30V	—	3A
	125V	7.5A	0.4A
	250V	7.5A	0.2A
C1	30V	—	3A
	125V	7.5A	0.5A
	250V	7.5A	0.25A
D	30V	—	7.5A
	125V	7.5A	7.5A
	250V	7.5A	3A

⑦	Gasket ガスケット	FKM	Oリング (S-50) 4種D
⑥	Diaphragm ダイヤフラム	SUS316L . PTFE	
⑤	Lower Box 下箱	SUS316	
④	Middle Box 中箱	SUS316	
③	Upper Box 上箱	Steel Cr Plating . SUS304 鉄クロムメッキ	
②	Socket 接続部	Brass . SUS	
①	Case ケース	ADC12	Munsell マンセル 7.5BG7/2
No.	Name 部品名	Material 材質	Finish 処理

Order No. 貴注番			
Scale Range 目盛範囲	MP a		
Quantity 台数			
Remarks 備考			
MATERIAL 材質	DESIGNED FOR 品名 Diaphragm-Seal Type Pressure Switch 隔膜式圧力スイッチ	PLATES NO. 品番	MODELS TO BE USED QTY.
FINISH 処理	MODEL AND SIZE 型名 PK-2 DK-F8	DATE 2024.05.28	CHKD. KONTANI
SCALE 尺 寸 Free	TOLERANCE 公差 ±	DRWN. HONDA	APPD. TANABE
TITLE 図名 Outside Drawing 外形図		DRWG NO. 図番 DKF8-PK2-001	